

CATEGORY: ANTI-VIBRATION PADS

RCR SERIES

Rubber-cork-rubber pad

7/8 in Thickness (22 mm)	15–55 psi Working range (103–379 kPa)	6 sizes Can be cut to size
------------------------------------	---	--------------------------------------

DESCRIPTION

- Low-density cork bonded between two ribbed neoprene layers.
- The cork adds isolation; the rubber faces provide excellent grip.
- Alternating high-low rib construction.
- Excellent sound attenuation.
- Simple field installation, no bolting required.

APPLICATION

- Where bolting is to be avoided.
- Minor, non-critical vibration conditions.
- Pumps, motors, air-conditioning units, generators, etc.
- Acoustic problem applications.

SELECTION TABLE

Size (in)	Rated load per pad (lb)	(kg)
2 x 2	200	91
3 x 3	450	204
4 x 4	800	363
6 x 6	1,800	816
12 x 12	7,200	3,266
18 x 18	16,000	7,257



RCR pad: ribbed neoprene faces with a cork core.

Note: Research and development is an ongoing process. As improvements are made, specifications and dimensions may change without notice. Dimensional tolerances conform to international standards.

DEFLECTION · Acoustics & vibration isolation
2480 boul. des Entreprises, Terrebonne, QC J6X 4J8
514 371-6669 · info@deflection.ca · deflection.ca