

Distributed by DEFLECTION.ca

– 514-371-6669 | Mickael@deflection.ca

Specification sheet manufactured by VIBRACAN

SN pads 2

model	elastomerique (inches)	acier (inches)
R ou N	9/16 (code 2)	–
SR ou SN	9/16	1/4
RSR ou NSN	9/16	1/4

dimensions (inches)	50 durometer		30 durometer	
	charges opt.	charges max.	charges opt.	charges max.
2.25 x 2.25	450	710	380	450
3.00 x 3.00	810	1260	540	810
3 x 4.50	1215	1890	810	1215
3 x 6.00	1600	2500	1080	1600
3 x 9.00	2400	3800	1600	2400
3 x 12.00	3200	5000	2160	3200
3.75 x 3.75	1250	1950	840	1250
4.50 x 4.50	1800	2800	1200	1800
5.25 x 5.25	2500	3800	1650	2500
6.00 x 6.00	3200	5000	2160	3200
6.00 x 9.00	4800	7600	3240	4800
6.00 x 12.00	6500	10 000	4320	6500
6.00 x 18.00	9700	15 000	6500	9700
6.75 x 6.75	4100	6400	2740	4100
7.50 x 7.50	5000	7900	3360	5000
8.25 x 8.25	6100	9500	4080	6100
9.00 x 9.00	7300	11 3000	4850	7300
9.00 x 12.00	9700	15 000	6500	9700
9.00 x 18.00	14 500	22 700	9750	14 500
9.75 x 9.75	8500	13 300	5700	8500
10.50 x 10.50	9900	15 500	6600	9900
11.25 x 11.25	11 400	17 700	7600	11 400
12.00 x 1200	13 000	20 000	8650	13 000
18.00 x 18.00	29 000	45 400	19 400	29 000

Note

Research and development is a continuous process with us as improvements are made from time to time, specifications / dimensions may change without notice. Tolerances in dimensions are as per international standards.

DISTRIBUTED BY:

DEFLECTION